

Page 2, please delete the eighth full paragraph and substitute with the following:

A9 There is described a dosage device with which the present drinks machine can be retrospectively fitted.

Page 2, after the eighth full paragraph, please add a new centered heading as follows:

Brief Description of the Drawings

Page 3, after description of Fig. 3, please add a new centered heading as follows:

Detailed Description of the Invention

IN THE CLAIMS:

Please delete Patent Claims at top of page.

At line 1, before claim 1, please insert --I Claim--.

1 (Amended). Drinks machine, in particular a coffee machine, with an entry device for solid cleaning agent, in particular in pressed form, comprising in combination an automatically dosing, enclosed dosage device (1) for the cleaning agent, said dosage device including a spout (10), a storage container (4) protected from the spout (10), and a dosage unit (8). 112 2nd

2 (Amended). Drinks machine according to Claim 1, wherein said dosage unit (8) contains at least one movable dosage chamber (9) through which a certain predetermined amount of cleaning agent can be fed from said storage container (4) into said spout (10).

3 (Amended). Drinks machine according to Claim 1, wherein said dosage unit (8) contains a sensor (17) in said spout (10) for determining the presence or absence of cleaning agent.

4 (Amended). Drinks machine according to Claim 3, wherein said dosage unit (8) contains a shut-off device (15) for said spout (10).

5 (Amended). Drinks machine according to Claim 4, wherein said shut-off device

(15) is arranged after said sensor (17) in the direction of flow.

6 (Amended). Drinks machine according to Claim 1, wherein said dosage unit includes a dosage wheel (7) with a number of dosage chambers (9) arranged at intervals to one another and which can be consecutively aligned flush with said spout (10).

7 (Amended). Drinks machine according to Claim 6, wherein said dosage wheel (7) can be driven about a vertical axis and which includes the lower boundary of said storage container (4) in the direction of gravity and that said spout (10) is arranged below said dosage wheel (7).

8 (Amended). Drinks machine according to Claim 7, wherein said dosage wheel (7) is formed as a disc and said dosage chambers (9) are formed as through-openings through said disc.

9 (Amended). Drinks machine according to Claim 6, and a scraper (11) is provided in the region above said spout (10) to protect said dosage chamber (9) aligned flush with said spout (10) from said storage container (4).

10 (Amended). Drinks machine according to Claim 1, and the application of cleaning agent in granular form.

11 (Amended). Drinks machine according to Claim 6, wherein said dosage chamber (9) is formed for only accepting one single granulate grain.

12 (Amended). Drinks machine according to Claim 6, wherein said dosage device (1) can be separated into parts, wherein said storage container (4) consists of a housing (4a) which can be removed from a base section (6), said base section (6) includes said dosage wheel (7) of said dosage unit (8), and said base section (6) can be removed from a beam (3) which includes the drive (13, 14) of said dosage wheel (7).

13 (Amended). Drinks machine according to Claim 1, and a device (15, 16, 17) for